SECTION

9

Aluminum	9-2	Zinc	9-14
Pistol Frame	9-2	Knot	9-14
Rocker Arm	9-2	Bracket	9-14
Right/Left Hand Bracket	9-2	Faucet Handle	9-14
Endbell	9-3	Connector	9-15
Engine Base Bracket	9-3	Kitchen Faucet Hub	9-15
Water Passage	9-3	Fuel Fitting	9-15
Heat Sink Front & Back	9-4	Reverse Valve Casket	9-16
Chassis	9-4	Casket Arm	9-16
B Pillar	9-4	Display Frame Component	9-16
Trimmer Deck Housing	9-5	Outside Cover	9-17
RFU Enclosure	9-5	Front Plate L-20	9-17
Impeller	9-5	Connector Housing	9-17
Lower Crankcase	9-6	Rearview Mirror Mount	9-18
Differential Carrier	9-6	Steering Wheel Ignition Lock Housing	9-18
Beta Crankcase Right & Left	9-6	Headlamp Visor	9-18
Scooter Monocoque Frame	9-7	Camera Bracket	9-19
Rear Wheel Drive Northstar Block Casting	9-7	ZA (Zinc-Aluminum)	9-20
Power Condition Module Chassis	9-7	Tool Housing & Components Transmission Shift Selector Tube	9-20
MMC Brake Drum	9-8		9-20
AWD Clutch Housing	9-8	transmission Shift Selector Tube	9-20
RWD Transmission	9-8		
Magnesium	9-9		
Frame	9-9		
Head Node	9-9		
Fishing Reel	9-9		
Clutch Cover	9-10		
Camera Assembly	9-10		
Hand-Held Computer Housing	9-10		
Gear Case Housing Assembly	9-11		
Lock Housing	9-11		
Fairing Support Bracket	9-11		
Seat Back and Cushion	9-12		
Lift Gate Inner Panel	9-12		
Cross Car Beam for Instrument Panel	9-12		
Oil Tank	9-13		
SAWZALL Gear Case Assembly	9-13		

Aluminum

Part Name: Pistol Frame

Application: 0.22 Caliber Pistol

Part Weight: 0.35 lbs.
Alloy: A380

Comments: Part was previously

machined from stock. This is the first aluminum die casting used by Smith & Wesson.

Customer: Smith & Wesson



Aluminum

Part Name: Rocker Arm

Application: Honda Civic Engine

Part Weight: 0.48 lbs.
Alloy: 383

Comments: Process improvements and

strict attention to detail resulted in cost savings on these high integrity, near porosity-free parts. The parts include a special "wear" insert chip and meet very tight specifications.

Customer: Honda of America Mfg., Inc.



Aluminum

Part Name: Right/Left Hand Bracket

Application: BRP Skidoo
Part Weight: 0.75 lbs.
Alloy: Aural-2

Comments: Part was previously made

from low pressure permanent mold with extensive machining. High vacuum die casting created a heat treatable and weldable part for structural application, requiring minimal machining. Overall piece price reduction was on the order of 40%.

Customer: BRP Skidoo



Aluminum

Part Name: Endbell

Application: Air Compressors


Part Weight: 0.85 lbs. Alloy: 380

Comments: Major tooling and process

improvements resulted in scrap reduction, increased cost savings, production and quality. Completed cast units highly competitive in the market against lower entry models produced using stamped steel.

Devilbiss Air Power **Customer:**

Company



Aluminum

Part Name: Engine Base Bracket **Application:** Honda Accord Engine

Part Weight: 6.2 lbs.

ADC3SF jointly developed with Honda, compatible with SF36, Aural 2 Alloy:

Comments:

Replacing a previously stamped, 16 piece part, the new part is 27 in. long, thin-walled, with screw bosses, eliminating the welding operation and reduced weight by

Customer: Honda



Aluminum

Part Name: Water Passage

Application: Honda Civic Engine

Part Weight: 1.4360 lbs. Alloy:

Comments:

The Water Pasage hose mating surface is cast to specifications allowing the shipping of the part to the customer without any machining to the snout. This tight tolerance allows a cost savings to the customer. The customer saves the cost of machining for the snout, which is estimated at a 23%

cost savings.

Honda of America Mfg. Inc. **Customer:**



Aluminum

Part Name: Heat Sink Front & Back


Application: Garmin G-1000 Flat Panel Flight Display

Part Weight: 1.91 lbs.
Alloy: 360

Comments: Parts are assembled to

collect & disperse heat from an LCD unit. Converted from machined parts to die castings. Increased production rate & reduced piece part cost. First time use of aluminum heat sink for this type of application. 360 alloy was selected based on it's corrosion resistance which protects the assembly from oxidation & other corrosion resulting from frequent atmospheric changes experienced by components used in general aviation. Painting or coatings are not required & are ready for assembly upon arrival at customer location.

Customer: Garmin International



Aluminum

Part Name: Chassis


Application: Human Transporter

Part Weight: 8.2 lbs.
Alloy: 380

Comments: The casting is produced to

net shape and meets strict specifications. True position tolerances on critical dimensions were reduced resulting in reductions in machining and substantial cost savings.

Customer: Segway



Aluminum

Part Name: B Pillar

Application: Automotive Structural

Support

Part Weight: 9.2 lbs.
Alloy: 380

Comments: A new part cast for automo-

bile body framing support application. Yields weight savings benefit over fabricated steel components.

Customer: -



Aluminum


Part Name: Trimmer Deck Housing **Application:** Walk Behind Trimmer

Part Weight: 9.2 lbs. Alloy: 380

Comments: As compared to a previous

die casting design and tooling design, newly designed tooling allowed for scrap reduction (34%), cycle time reduction (52 sec.) and weight reduction (2 lbs.).

Garden Way, Inc. **Customer:**



Aluminum

Part Name: RFU Enclosure

Application: Microwave Communications

Part Weight: 15.8 lbs. 413 Alloy:

Comments:

Formerly produced as an investment casting. Provides heat dissipation and electrical conductivity. Die casting reduced lead time and machining requirements.

Harris Corporation, **Customer:**

Microwave Communications

Division



Aluminum

Part Name: Impeller

Application: Industrial/Commercial

Blower


Part Weight: 10.29 lbs A380 Alloy:

Comments:

Impeller used in industrial and commercial blowers. The application of the die cast part enabled the unit to operate at higher speeds, with less noise, while reduc-ing the amount of secondary

machining.

Ametek Rotron **Customer:**



Aluminum

Part Name: Lower Crankcase


Application: Motorcycle 16.31 lbs. **Part Weight:**

Alloy: LM2 to JVM Specifications

Comments: Redesign of original T120,

1959 Bonneville high performance version of Triumph's 650cc twin. Eliminated costly secondary machining operations, additional engine parts and fully utilized the benefits of high pressure die casting process.

Triumph Motorcycles **Customer:**



Aluminum

Part Name: Differential Carrier

Application: Independent Rear

Suspension

Part Weight: 16.5 lbs.

ADC-12 -T6 Heat Alloy:

Treatment

Comments: Past generation was an iron

casting. First high volume squeeze casting used in an independent rear suspension axel carrier. Squeeze casting decreased weight by 22 pounds over cast iron

process.

Visteon Corporation **Customer:**



Aluminum

Beta Crankcase Right & Left **Part Name:**


Application: Motorcycle 16.8 lbs.

Part Weight: Alloy: 383

Comments:

These net-shape, complex castings were converted from the permanent mold process to meet stringent specifications of improved quality, pressure tightness, cosmetic appearance, higher volume and cost reductions.

Customer: Harley-Davidson



Aluminum

Part Name: Scooter Monocoque Frame

Application: Honda Scooter Super Sport

Part Weight: 23.4 lbs.

Alloy: JIS ADC12; 383 equivalent

Comments: Previously fabricated from steel sheet stamping and

pipes. Die casting provided weight savings and cost

reduction.

Honda R&D Co., Ltd. **Customer:**



Aluminum


Rear Wheel Drive Northstar Block Casting **Part Name:**

Rear Wheel Drive Northstar Engine **Application:**

79.83 lbs. **Part Weight:** A380 Alloy:

Comments:

Customer: GM Powertrain



Aluminum

Power Conditioning Module Chassis **Part Name:**


Application: Computer/Electronics

Part Weight: 2.3 lbs. 380 Alloy:

Comments:

Originally machined from a roughly shaped ingot, this chassis gained sig-nificant cost savings after being converted to an aluminum die casting.

Novatel Wireless **Customer:** Technologies, LTD



Aluminum

Part Name: Aluminum MMC Brake Drum

Application: Commercial, Military, and

Special Vehicles

Part Weight: 38.5 lbs. A356.2 Alloy:

Comments: Originally produced in

cast iron. A unique horizontal squeeze cast process allowed a selectively placed ceramic preform to be infiltrated, creating a selectively reinforced, Metal Matrix Composite (MMC) aluminum brake drum. The new brake drum weights at least 45% less.

Century 3+ Inc. **Customer:**



Aluminum

Part Name: Automotive AWD

Clutch Housing

Application: Automotive

Part Weight: ADC12-T5 Alloy:

Comments: Originally produced as a

2.4 lbs.

multi-step forged steel hous-ing, but this part was successfully convert this part to an aluminum squeeze casting. The new squeeze cast design incorporated 33 spline teeth with 0.1 degree draft. A significant mass reduction was obtained resulting in better fuel efficiency and reduced inertia for improved all wheel drive engagement response time.

Borg Warner TTS, PTC **Customer:**



Aluminum


Part Name: RWD Transmission **Application:** Automobile Industry

Part Weight: 37.4 lbs. A380 Alloy:

Comments:

Utilizes a unique process, involving 2 cast-in steel tubes, which have to be inserted in the ejector die and maintain location.

Customer: Chrysler



Magnesium

Part Name: Frame

Application: Novatel Expedite Modem

Part Weight: 0.01 lbs. AZ91D Alloy:


Comments: Converted from a plastic

part. The magnesium casting eliminated a plastic part sandwiched between two metal plates and held together with self tapping screws, resulting in cost sav-

ings to the customer.

Novatel Wireless **Customer:**

Technologies, LTD



Magnesium

Part Name: Head Node

Application: Mountain Bike

Part Weight: 0.22 lbs. Alloy: AZ91D

Comments: Originally designed as two

aluminum investment cast parts, this unique die cast mag design and application yields a 30% weight sav-ings, part and assembly cost savings, better consistency in impact and fatigue and

better performance.

Cannondale **Customer:**



Magnesium

Part Name: Fishing Reel

Application: Ardent XS Fishing Reel


Part Weight: 31.3 grams AZ91D Alloy:

Converted from plastic & **Comments:**

die cast aluminum components. Complex geometry & varying wall thickness. Tooling uses 3 slides to form entire exterior of part. Tight tolerance machining of bores and surfaces for mating components. 100% made in USA (Components

& Assembly).

Marsh Technologies, Inc. **Customer:**



Magnesium

Part Name: Clutch Cover

Application: All Terrain Vehicle Clutch

Part Weight: 0.44 lbs.

Alloy: AZ91D

Comments: A conversion from aluminum

die casting to magnesium die casting resulted in a weight reduction of 45% and a significant cost reduction by eliminating machin-

ing.

Customer: Polaris Industries, ATV Div.



Magnesium

Part Name: Camera Assembly

Application: Digital Camera

Part Weight: 0.48 lbs.

Alloy: AZ91D

Comments: Originally designed as aluminum investment cast

aluminum investment cast parts, the design complexity and required precision mandated a transition to magnesium die cast parts.

Customer: Eastman Kodak



Magnesium

Part Name: Hand-Held Computer

Housing

Application: Hand-Held Computer

Part Weight: Over 0.5 lbs.

Alloy: AZ91D

Comments: -

Customer: Telxon Corporation



Magnesium

Part Name: Gear Case Housing

Assembly

Automatic Power Pruner Application:

Part Weight: 0.64 lbs. Alloy: AZ91D

Comments: Magnesium was chosen

for it's strength and low weight for this application over plastic and aluminum.

Bearing diameter tolerances of 0.001" are required and eliminate machining and

masking cost.

Customer: Echo



Magnesium

Part Name: Lock Housing


Application: SUV Tilt Steering Column

Part Weight: 2.02 lbs. Alloy: AM60B

Comments:

This die casting controls the tilt/telescoping features in the steering column and incorporates the ignition switch, shift lever and brake-shift interlock into one casting. In addition to tight casting. In addition to tight dimensional control, the higher elongation in AM60B alloy provides good crash energy management.

Visteon/Ford **Customer:**



Magnesium

Part Name: Fairing Support Bracket

Application: Buell 1125R Superbike

Part Weight: 2.71 lbs. Alloy: AZ91D

Comments: This bracket provides sup-

port for the motorcycle's instrument cluster, windshield/cowling, direction signals and rearview mirror with increase copacity and a cost savings of aproximatly 26%.

Customer: Buell Motercycle Co.



Magnesium


Part Name: Seat Back and Cushion

Luxury Car Seat Back and **Application:**

Cushion **Part Weight:**

Alloy: AM60B

Comments: Customer:



Magnesium

Part Name: Vehicle Lift Gate

Inner Panel

Application: Automotive **Part Weight:** 18 lbs. AM60 Alloy:

Comments:

Replacing a stamped steel assembly, this large die cast magnesium lift gate reduced weight, added design flexibility and reduced assembly time through the integration of various components. The various components. The die cast lift gate is 54 x 52

inches.

Ford Motor Co. **Customer:**



Magnesium

Part Name: Cross Car Beam for

Instrument Panel

Application: General Motors Medium

Duty Trucks


Part Weight: 21.5 lbs. Alloy: AM60B

Comments: An example of maximizing

the die casting process, machine and die to obtain substantial cost savings. The improvements resulted in weight savings & cost reductions through decreased material, downtime, and elimination of machining/

repair.

General Motors Truck **Customer:**



Magnesium

Part Name: Oil Tank Snowmobile **Application:** Part Weight: 2.03 lbs. AZ91D Alloy:

Comments:

This magnesium oil tank replaces one that was a stamped aluminum and brazed assembly. The case is comprised of 3 separate magnesium die castings. It is lighter and more tunable than the aluminum it replaces.

Customer: Arctic Cat Inc.



Magnesium

Part Name: SAWZALL Gear Case Assembly

Power Tool **Application: Part Weight:** .293 lbs. Alloy: AZ91D

Comments: Met customer requirements

of eliminating machining and reducing cost of similar aluminum castings. Magnesium die casting holds dimensional tolerances that eliminate the need to machine.

Customer: Milwaukee Electric Tool Co.



Zinc

Part Name: Knot


Application: Marketing **Part Weight:** 5.5 Grams

Alloy: ZP5

Comments:

This item's shape has never been industrially manufac-tured and displays ingenious part and tooling design.

Customer: Nyrstar



Zinc

Part Name: Bracket


Application: Electronics Enclosure

Part Weight: 15.42 Grams Alloy: Zamak No. 3

Comments: Converted from a machined

aluminum alloy resulting in cost savings. The part is cast to net-shape thereby totally eliminating any machining.

Customer:



Zinc

Part Name: Faucet Handle

Application: Two Handle Lavatory Faucet

Part Weight: 119 Grams Alloy: Zamak No. 3

Comments:

Major cost savings were achieved from tooling changes, which eliminated trimming, reduced polishing the parting line and machining

ing operations.

Customer: Delta Faucet Company



Zinc

Part Name: Connector

Application: "TERA" Connector


Part Weight: 0.4 oz.

Alloy: Zamak No. 3

Comments:

Die casting offered superior EMI shielding and mechani-cal integrity at a favorable

Siemon Company **Customer:**



Zinc

Part Name: Kitchen Faucet Hub Pull-Out Faucet **Application:**

Part Weight:

Alloy: Zamak No. 3

Comments:

Delta Faucet Company **Customer:**



Zinc

Part Name: Fuel Fitting

Application: Dragon Fly™ Cook Stove

Part Weight: 0.5 oz.

Zamak No. 3 Alloy:

Comments:

Originally designed as an assembly of three screw-machined components. Converting the component to die cast Zamak 3 provided a cost reduction and allowed for the street living. for the streamlining.

Customer: Mountain Safety Research



Zinc

Part Name: Reverse Valve Casting

Application: Snap-On Tools

Part Weight: 1.06 oz.


Alloy: Zamak No. 5

Comments: Exceedingly complex,

high tolerance die casting

produced in high volumes & requiring minimum machining. Zinc die casting selected over powder metallurgy, machining & metallinjection molding because of lower production costs.
50 mils to 230 mils casting thickness & a stepped hole (to a final ID of 0.3000") extending the length of the cylinder with minimum draft.

Customer: Vic Royal



Zinc

Part Name: Casket Arm

Application: Casket **Part Weight:** 3.5 oz.

Alloy: Zamak No. 3

Comments:

This precisely cored zinc die casting provides the right amount of friction with the hinge to allow the lift bar to remain in the position it was last set. Was a steel

stamping.

Customer: Vic Royal



Zinc

Part Name: Display Frame Component


Application: Store Display Unit

Part Weight: 26.16 oz. Zamak No. 3 Alloy:

Comments: Conversion from a steel

weldment to a die casting resulted in substantial cost savings. The casting is used as the frame for a track running shoe display rack.

Customer: CDC Marketing



Zinc

Part Name: Outside Cover

Power Lever Door Lock **Application:**

Part Weight: 3.0 lbs.


Zamak No. 3 Alloy:

Comments: Converted from a perma-

nent mold casting, these die cast parts offer thinner walls, less prep for plating due to the extraordinary surface finish and cost savings

(39%).

Mas-Hamilton Group **Customer:**



Zinc

Part Name: Front Plate L-20

Telecommunications Exten-**Application:**

sion Shelf


Part Weight: 3.53 oz. Za4Cu1 Alloy:

New part for mounting opti-**Comments:**

cal and electrical cartridges. Challenge of fill very thin walls and narrow (0.2 mm) flatness tolerance. Success related to vacuum technology, die thermal conditioning and precision and sprue

runner design.

Customer: ALCATEL ITALIA S.p.A.



Zinc

Part Name: Connector Housing **Application:** Fiber Optic Transceiver


Part Weight: 0.19 oz.

Alloy: Zamak No. 2

Comments:

Previously produced from multiple machined cast metal or sheet metal fabri-cated parts, which lacked precision for speedy assembly of components. Cost savings in material, production methods and labor were achieved with the conversion to die casting.

Customer: Agilent Technologies



Zinc

Part Name: Rearview Mirror Mount

Windshild-to-mirror head **Application:**

transition housing


Part Weight: 4.1 oz.

Alloy: Zamak No. 5

The part was designed around the mirror mount's **Comments:**

humidity sensor for the smallest possible footprint.

Customer: Gentex Corporation



Zinc

Application:

Part Weight:

Steering Wheel Ignition and Lock Housing **Part Name:**

Automotive 13.9 oz


Alloy: Zamak #5

Comments: The ignition and lock hous-

ing is a safety-critical com-ponent of the automotive steering column. It keeps the steering wheel locked until the car is ready to start and drive.

Customer: Valeo Sisitemas

Electronics, SA de CV



Zinc

Part Name: Headlamp Visor

Application: Harley-Davidson Motor-

cycle

2.78 lbs. **Part Weight:** Alloy ZA8

Combined two parts **Comments:**

into one to reduce cost and part numbers. As the center point of the integrated motorcycle handlebar assembly it needs to be functional and aesthetic. Carefully controlled process produces a surface finish conducive for a highly cosmetic chrome plate finish.

Customer: Harley-Davidson



Zinc

Part Name: Bracket, Camera, ASIC

Infrared Interactive Whiteboard **Application:**

Part Weight: 0.065 oz. Zamak #3 Alloy

Comments:

This zinc die casting replaces an ABS plastic part. It improves the product durability and performance. The casting is used to hold an infrared camera ridigly in place on an interactive whiteboard. This whiteboard connects to a computer and employs infrared light to locate all interactions with the whiteboard.

SMART Technologies Customer



ZA (Zinc-Aluminum)

Tool Housing & Components **Part Name:**

Air-Powered Hand Tool

Part Weight:


Application:

ZA-8 and **ZA-27** Alloy:

Comments:

The components for this air ratchet tool consist of two die cast ZA-27 split halves incorporating as-cast "grip" surface embossing, logos and identification and a one-piece ZA-8 air manifold that does not require machining. ZA alloys allowed wall thicknesses of 0.060 inch for the handles and enhanced sound suppression for quieter operation. Previously an assembly of a machined steel head and a cast aluminum handle housing that required extensive machining was used.

Customer: Snap-On



ZA (Zinc-Aluminum)

Transmission Shift Selector **Part Name:**

Tube Unit

Passenger Car & Light Truck **Application:**

Part Weight: 1.1 lb. Alloy: ZA-8

This single die casting **Comments:**

replaced a four piece assembly and resulted in an estimated 50% cost savings.

Customer:

